

MBB Series

435W/440W/445W/450W/455W/

CUPV72M-H

MBB HALF-CELL MONO PV MODULE



COMPREHENSIVE CERTIFICATES

IEC61215 / IEC61730 / IEC61701 / IEC62716 / IEC62804
ISO 9001: 2015 Quality management systems;
ISO 14001: 2015 Environmental management systems;
OHSAS 18001: 2007 Occupational health and safety management systems;

KEY SALIENT FEATURES



High output power



Better power generation under shadows



Strong anti-hot spot ability



Strong mechanical load capacity



Super strong frame



1500V system voltage

SUNPARK ECO ENERGY


Sunpark will initiate the second phase of our development strategy. Our company regards "reasonable prices, efficient production time and good after-sales service" as our tenet. We hope to cooperate with more customers for mutual development and benefits. We welcome potential buyers to contact us.

QUALIFICATIONS AND CERTIFICATES



LINEAR PERFORMANCE WARRANTY

- 12 Years Manufacturing Warranty
- 12 Years 90% Power Output
- 25 Years 80% Power Output




SUNPARK ECO ENERGY SYSTEMS
www.chinasunpark.com




MBB Series CUPV72M-H

MECHANICAL DRAWINGS




I-V CURVES

I-V Curves at SUN440-72M-H6 at different Irradiances



Power voltage current curve at different temperature



MECHANICAL SPECIFICATION

Cell Type	Mono Crystalline 166x83mm
Number Of Cells	144 (6x24)
Dimensions(AxBxC)	2108x1048x35mm
Weights	24.5kg
Glass	3.2mm Tempered Low Iron Glass
Aluminium Frame	Anodised Aluminium
Junction Box	Split Junction Box (IP68 ,three diode)
Connector	Mc4 Compatible
Output Cables	4.0mm²,+300mm,-300mm Customized Length

PACKING CONFIGURATION

Container	40' HQ
Pieces Per Pallet	30
Pallets Per Container	22
Pieces Per Container	660

ELECTRICAL CHARACTERISTICS

Module Type	435W		440W		445W		450W		455W	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power At STC(Pmax)	435W	327.0W	440W	330.7W	445W	334.5W	450W	338.3W	455W	342.0W
Short Circuit Current(Isc)	11.14A	9.00A	11.21A	9.06A	11.29A	9.12A	11.36A	9.18A	11.43A	9.24A
Open Circuit Voltage(Voc)	49.2V	45.9V	49.4V	46.1V	49.7V	46.3V	50.0V	46.6V	50.3V	46.9V
Maximum Power Current(Imp)	10.66A	8.53A	10.73A	8.59A	10.80A	8.65A	10.87A	8.70A	10.94A	8.75A
Maximum Power Voltage(Vmpp)	40.8V	38.3V	41.0V	38.5V	41.2V	38.7V	41.4V	38.9V	41.6V	39.1V
Module Efficiency	19.69%		19.92%		20.14%		20.37%		20.60%	
Power Tolerance	0~+5W		0~+5W		0~+5W		0~+5W		0~+5W	
Maximum System Voltage	VDC 1500V									
Maximum Series Fuse	20A									
Increased Snowload Acc.to Iec 61215	5400Pa									
Operating Temperature	-40~+85°C									
Number Of Bypass Diodes	3									
Norminal Operating Cell Temperature(Noct)	45°C±2°C									
Temperature Coefficient Of Pmax	-0.36%/°C									
Temperature Coefficient Of Voc	-0.29%/°C									
Temperature Coefficient Of Isc	0.05%/°C									

STC: 1000W/m2 irradiance, 25°C cell temperature, AM1.5. NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, wind speed 1m/s.